

Infinity Channel Specification Item

Supply and installation of "Infinity" waterproof double slit drainage channel. (Art. INF/C150, INF/C300, INF/C450). The channel is made of Polypropylene (PP). Minimum thickness 3 mm, standard height 12.5 cm with internal slope and infinitely modular. The body of the channel is reinforced by fins, both longitudinally and transversely, which give it rigidity and strength, while peripherally, on the outer top, it is equipped with a felted fabric permitting the mechanical attachment of the waterproofing system. Please note: To perform the connection between the waterproofing system and the channel follow the manufacturer's instructions of waterproofing products and always use the junction strip (art. INF / BAND12). The tileable type grid in the upper part is provided with a felted fabric that allows the mechanical attachment of the tile using commercially available adhesives.

Please note: Follow adhesive manufacturer's directions in order to use the correct adhesive. The channel-grid system presents two drain slits sized in mm and it is provided with drain terminals (Art. INF/S50, INF/S75A, INF/S75B, INF/S90) and end pieces (INF/T100) compatible with the channel by means of a male/female coupling equipped with lip seal and through a mechanical flange equipped with an additional flat silicone seal, reinforcement plates, screws and bolts.

DESCRIPTION	Article	ML	€/ML	€/TOTAL
* Channel body-element 1 (L=1500mm.)	INF/C150			
** Channel body-element 2 (L=1500mm.)	INF/C300			
** Channel body-element 3 (L=1500mm.)	INF/C450			
Tileable pedestrian grating stainless steel AISI 304 (L=1500mm.)	INF/GP304			
Tileable pedestrian grating stainless steel AISI 316L (L=1500mm.)	INF/GP316			
Walkable solid grating brushed stainless steel AISI 304 (L=1500mm.)	INF/G304			
Walkable solid grating brushed stainless steel AISI 316L (L=1500mm)	INF/G316			
Sealing tape H 120mm - Rolls = 20mt.	INF/BAND12			

* Element consecutive to article No. INF/C150 ** Element consecutive to article No. INF/C300

DESCRIPTION	Article	QTY.	€/PIECE	€/TOTAL
Tileable pedestrian grating stainless steel AISI 304 (L=200mm.)	INF/GP304/20			
Tileable pedestrian grating stainless steel AISI 316L (L=200mm)	INF/GP316/20			
Walkable solid grating brushed stainless steel AISI 304 (L=200mm.)	INF/G304/20			
Walkable solid grating brushed stainless steel AISI 316L (L=200mm)	INF/G316/20			
Head	INF/T100			
* Run-off pipe/Drain terminal Ø50 mm. DN 50	INF/S50			
** Run-off pipe/Drain terminal Ø75 mm. DN 75 A	INF/S75A			
*** Run-off pipe/Drain terminal Ø75 mm. DN 75 B	INF/S75B			
*** Run-off pipe/Drain terminal Ø90 mm. DN 90	INF/S90			
End plug Ø50 mm. DN 50	INF/TA50			
End plug Ø50 mm. DN 75	INF/TA75			
The kit includes: screws, bolts, flat seal, connecting plates, key	INF/KIT			

* Compatible with article No. INF/C150 ** Compatible with article No. INF/C300 *** Compatible with article No. INF/C450
Articles: INF/GP316 - INF/G316 - INF/GP316/20 - INF/G316/20 are only available on request.